



Xunison Hub D50

AX5400

Wi-Fi 6 Mesh Router

- 4*4 MU-MIMO
- Rapid one-button pairing
- Parental Control
- Remote access management



Faster Wi-Fi

Anytime, Anywhere

Product Introduction

The Xunison Hub D50 is a robust dual-band Mesh Wi-Fi system with the latest Wi-Fi 6 technology, faster than Wi-Fi 5(ac) technology. The product supports many connected devices providing a stable and uninterrupted internet connection.

The MU-MIMO and beamforming function ensure a high data rate and signal quality supporting multiple simultaneously connected devices.



Support 802.11 a/b/g/n/ac/ax

Latest wireless technology with backward compatibility



High-Speed Wi-Fi 6

AX5400, MU-MIMO, Mesh Capability




High-Performance Antennas

Wi-Fi antennas (internal), Multi-frequency coverage



Security Assurance

Stable firewall, Multiple filtering rules Multiple security protocols



Wi-Fi Mesh

Provides increased Wi-Fi coverage and eliminates the dead zones



Bracken Business Park, Bracken Rd, Sandyford Business Park, Sandyford, Dublin, Ireland

www.xunison.com



Xunison Hub D50

SPECIFICATIONS

Data Range	2.4GHz 40MHz 2ss: 573Mbps
	5GHz 160MHz 4ss: 4804Mbps
Wireless LAN	Support 802.11 a/b/g/n/ac/ax standards
	2.4GHz/5GHz frequency range
	20/40/80/160 MHz bandwidth
	Channel adaption
	MSSID + Guest network
	WPS: PBC/PIN modes
	WPA/WPA2/WPA3 security
	AP Isolation/SSID Isolation
SSID and WAN binding	
Wi-Fi Mesh	Wi-Fi son/Easy MESH*
	One-button Matching
Wi-Fi Antennas	External 2*2 2.4GHz & 5GHz & 4*4 5GHz antennas
	Gain: 3dBi
Operation Mode	Bridge
	Route
Firewall	Built-in NAT firewall
	Firewall level setting*
	Defense of DoS ARP attacks/Port scan
	DHCP/ARP/IGMP message suppression*
	MAC/URL filtering
	Inflow/outflow filtering of IP/Protocol/Port
Quality of Service control	802.11e WMM
	Classification of service flow*
	DSCP/802.1 p*
	SP and WRR mode*
	Port/VLAN/ IP rate limitation



Bracken Business Park, Bracken Rd, Sandyford Business
Park, Sandyford, Dublin, Ireland

www.xunison.com



Xunison Hub D50

Network Protocols and Features	Connection modes: PPPoE/DHCP/Static
	IPv4, IPv6, IPv4/IPv6
	DHCP v4/v6 server
	Static (v4/v6) routing
	NAT/ALG/DMZ/virtual server
	ARP/ICMP/DNS proxy
	Dynamic Domain Name System (DDNS)
	IGMP snooping and IGMP proxy*
	MLD snooping and MLD proxy*
	NTP
	VLAN
	VPN
Management	WebUI local management
	TR069/SNMP remote management
	Online and local software update/rollback
	Configuration data upload and download
	Local and remote diagnostic
Physical Interface	WAN port-RJ45 1*GE
	LAN ports-RJ45 4*GE
	USB2.0 port
	Power port
Buttons	WPS/MESH
	RESET
	On/Off
LED Indicators	Mesh indicator
	Wi-Fi indicator
	WAN indicator
	LAN indicator
	Internet indicator
	System indicator
	Power indicator



Bracken Business Park, Bracken Rd, Sandyford Business
Park, Sandyford, Dublin, Ireland

www.xunison.com



Xunison Hub D50

Physical Specification	Dimensions: 113.8*95.4*186mm
	Operating temperature: -10°C to 45°C
	Storage temperature: -40°C to 70°C
	Humidity: 5% – 95% (non-condensing)

Package Includes	Xunison Hub D50
	Quick Start Guide
	Power Adapter
	Ethernet Cable

DEVICE IMAGES



DEVICE IDENTIFICATION

Brand	Xunison
Device name	Xunison Hub D50
SKU:	RE-NN-D4-QC-122
Part Number	R-D50-1G-DB4-EM
Barcode	0754590921817
Serial Number	0101220083XXXXXX



Bracken Business Park, Bracken Rd, Sandyford Business
Park, Sandyford, Dublin, Ireland

www.xunison.com